



OMEGA 700 WH

Cod. **02003010**



INFORMACIÓN GENERAL

Subfamily	Chimney
-----------	---------

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (Energy efficiency class)	C
FDE (Fluid dynamic efficiency)	17,8
FDE class (Fluid dynamic efficiency class)	D
LE (Light efficiency) (lux/W)	26
LE class (Light efficiency class)	B
GFE (Grease filtering efficiency)	90,3
GFE Class (Grease filtering efficiency class)	B
Normal mode airflow MIN (m3/h)	385
Normal mode airflow MAX (m3/h)	645
Normal mode acustic power MIN (dB)	57,8
Normal mode acustic power MAX (dB)	71,8
Po (Off-mode power consumption) (W)	0
Ps (Stand-by power consumption) (W)	0

Integration directive EU 66/2014

<i>f</i> (Factor Increase in the time)	1,4
EEl (Energy efficiency Index)	81,3
QBEP (Maximum airflow point efficiency) (m3/h)	371,8
WBEP (Electrical power consumption at maximum efficiency) (W)	182,5
WL (Rated power lighting system) (W)	3

External Dimensions

Width (mm)	700
Depth (mm)	500
Maximum Total Height (mm)	1020
Minimum Total Height (mm)	720
Outlet Diameter (mm)	150, 125

Characteristics

Motor Quantity	1
Motor Model	TA
Maximum Pressure (Pa)	430
Filter Technology	Aluminium mesh
Booster	-
Power levels	3
Timer	-
Filter Saturation Indicator	lse
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	-
Remote control	-
Display	-

Lighting

Lightning Technology	LED
----------------------	-----

Installation

Minimum distance to an electric cooktop (mm)	650
Charcoal Filter	-
Inner shield	-

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50
Rated power input (W)	273
Protection against electric shock	Class II

Power cord length (m)	0,7
-----------------------	-----

Accessories

Upper Decorative Duct Extension	02862001
White Decorative Duct	No
Black Decorative Duct	No
Island Tube Enhancer	No
Back Draught Shutter	02832001
MAX PRO Metal Filter	02800917
Active Charcoal Filter	02859391
Noiseless Flexible Duct	02893002
Recirculating kit	02894000
