



CG5-T900 X

Cod. 02008299

EAN 8422248108102



INFORMACIÓN GENERAL

| | |
|-----------|---------------|
| EAN/UPC | 8422248108102 |
| Subfamily | Curved Glass |

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|---|------|
| AEC (Energy consumption per year) (kWh/año) | 48 |
| EEl class (Energy efficiency class) | B |
| FDE (Fluid dynamic efficiency) | 222 |
| FDE class (Fluid dynamic efficiency class) | C |
| LE (Light efficiency) (lux/W) | 4933 |
| LE class (Light efficiency class) | A |
| GFE (Grease filtering efficiency) | 8287 |
| GFE Class (Grease filtering efficiency class) | C |
| Normal mode airflow MIN (m3/h) | 296 |
| Normal mode airflow MAX (m3/h) | 495 |
| Normal mode acustic power MIN (dB) | 455 |
| Normal mode acustic power MAX (dB) | 66 |
| Po (Off-mode power consumption) (W) | 0 |

Integration directive EU 66/2014

| | |
|---|------|
| f (Factor Increase in the time) | 12 |
| EEl (Energy efficiency Index) | 644 |
| QBEP (Maximum airflow point efficiency) (m3/h) | 2875 |
| PBEP (Maximum pressure point efficiency) (Pa) | 288 |
| WBEP (Electrical power consumption at maximum efficiency) (W) | 1036 |
| WL (Rated power lighting system) (W) | 3 |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 148 |

External Dimensions

| | |
|---------------------------|-----|
| Width (mm) | 900 |
| Depth (mm) | 470 |
| Maximum Total Height (mm) | 776 |
| Minimum Total Height (mm) | 426 |
| Outlet Diameter (mm) | 150 |

Characteristics

| | |
|----------------------------------|------------------------|
| Motor Quantity | 1 |
| Motor Model | TT500 |
| Maximum Pressure (Pa) | 435 |
| Filter Technology | Aluminium mesh |
| Control Tecnology | Mechanical push button |
| Booster | 310 |
| Power levels | 3 |
| Timer | - |
| Filter Saturation Indicator | - |
| Charcoal Filter Change Indicator | - |
| Dimmer Function | - |
| Connectivity | No |
| Remote control | - |
| Display | - |

Lighting

| | |
|----------------------|---------------------|
| Light Model | ECOLED |
| Lightning Technology | Packaging Procedure |

Installation

| | |
|--|-----|
| Minimum distance to an electric cooktop (mm) | 650 |
| Minimum distance to a gas cooktop (mm) | 650 |
| Recirculation Option | √ |
| Charcoal Filter | - |

| | |
|----------------------|----------|
| Back Draught Shutter | Included |
| Inner shield | - |

Electric Connection

| | |
|-----------------------------------|---------|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 123 |
| Protection against electric shock | Class I |
| Plug type | Type F |

Accessories

| | |
|-------------------------|----------|
| Active Charcoal Filter | 02859492 |
| Noiseless Flexible Duct | 02893002 |
