




TFH 6430 GWH

Cod. **02010009**

EAN **8422248343619**



- ✓ Panel de Control táctil con display digital, temporizador de desconexión automática e indicador de limpieza de filtros
- ✓ 4 niveles de extracción, 3 + 1 TURBO
- ✓ Capacidad de extracción máxima - mínima (Reg.(UE) nº65/2014): 391m3/h
- ✓ 164m3/h
- ✓ Nivel sonoro (Reg.(UE) nº65/2014):44dB(A), máximo: 62dB(A)
- ✓ Motor Brushless. Extra silencioso. Consumomáximo de energía 53W
- ✓ Iluminación de alta eficiencia mediante tira LED regulable en intensidad
- ✓ Clase de eficiencia energética: A+



INFORMACIÓN GENERAL

EAN/UPC	8422248343619
Subfamily	Telescopic

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	13,4
EEL class (Energy efficiency class)	A+
FDE (Fluid dynamic efficiency)	24,9
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	18
LE class (Light efficiency class)	C
GFE (Grease filtering efficiency)	79,9
GFE Class (Grease filtering efficiency class)	C
Normal mode airflow MIN (m3/h)	164,1
Normal mode airflow MAX (m3/h)	320,4
Boost mode airflow (m3/h)	391,5
Normal mode acoustic power MIN (dB)	44
Normal mode acoustic power MAX (dB)	62
Boost mode acoustic power (dB)	65
Po (Off-mode power consumption) (W)	0,45
Ps (Stand-by power consumption) (W)	0

Integration directive EU 66/2014

f (Factor Increase in the time)	1,1
EEL (Energy efficiency Index)	41,5
QBEP (Maximum airflow point efficiency) (m3/h)	164,6
PBEP (Maximum pressure point efficiency) (Pa)	152
WBEP (Electrical power consumption at maximum efficiency) (W)	27,9
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	54

External Dimensions

Width (mm)	598
Depth (mm)	320
Maximum Total Height (mm)	182
Minimum Total Height (mm)	182
Outlet Diameter (mm)	150

Characteristics

Motor Quantity	1
Motor Model	EY400 395 b
Filter Technology	Aluminium mesh
Control Technology	Electronic Touch Control
Booster	✓
Power levels	4
Timer	-
Filter Saturation Indicator	✓
Charcoal Filter Change Indicator	-
Dimmer Function	✓
Connectivity	No
Remote control	-
Display	Display

Lighting

Light Model	SSLED
Lighting Technology	LED

Installation

Minimum distance to an electric cooktop (mm)	550
Minimum distance to a gas cooktop (mm)	650

Recirculation Option	-
Charcoal Filter	√
Back Draught Shutter	No
Inner shield	-

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Protection against electric shock	Class I
Plug type	No plug

Accessories

Active Charcoal Filter	02859394
Noiseless Flexible Duct	02893002
