




## S PLUS 7010 X

Cod. **02021602**

EAN **8422248093446**



### INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248093446 |
| Subfamily | Box           |

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|                                               |       |
|-----------------------------------------------|-------|
| AEC (Energy consumption per year) (kWh/año)   | 100,9 |
| EEl class (Energy efficiency class)           | C     |
| FDE (Fluid dynamic efficiency)                | 16,3  |
| FDE class (Fluid dynamic efficiency class)    | D     |
| LE (Light efficiency) (lux/W)                 | 22,5  |
| LE class (Light efficiency class)             | B     |
| GFE (Grease filtering efficiency)             | 88,5  |
| GFE Class (Grease filtering efficiency class) | B     |
| Normal mode airflow MIN (m3/h)                | 361   |
| Normal mode airflow MAX (m3/h)                | 637   |
| Normal mode acustic power MIN (dB)            | 69    |
| Normal mode acustic power MAX (dB)            | 74    |
| Po (Off-mode power consumption) (W)           | 0     |

### Integration directive EU 66/2014

|                                                               |       |
|---------------------------------------------------------------|-------|
| f (Factor Increase in the time)                               | 1,4   |
| EEl (Energy efficiency Index)                                 | 82,4  |
| QBEP (Maximum airflow point efficiency) (m3/h)                | 375,3 |
| PBEP (Maximum pressure point efficiency) (Pa)                 | 295   |
| WBEP (Electrical power consumption at maximum efficiency) (W) | 188,8 |
| WL (Rated power lighting system) (W)                          | 6     |
| EMIDDLE (Average illuminance on the cooking surface) (lux)    | 135   |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 900      |
| Depth (mm)                | 500      |
| Maximum Total Height (mm) | 1045     |
| Minimum Total Height (mm) | 730      |
| Outlet Diameter (mm)      | 150, 125 |

### Characteristics

|                                  |                        |
|----------------------------------|------------------------|
| Motor Quantity                   | 1                      |
| Motor Model                      | TA                     |
| Filter Technology                | Aluminium mesh         |
| Control Tecnology                | Mechanical push button |
| Booster                          | -                      |
| Power levels                     | 3                      |
| Timer                            | -                      |
| Charcoal Filter Change Indicator | -                      |
| Dimmer Function                  | -                      |
| Connectivity                     | No                     |
| Remote control                   | -                      |
| Display                          | -                      |

### Lighting

|                      |       |
|----------------------|-------|
| Light Model          | CSLED |
| Lightning Technology | LED   |

### Installation

|                                              |     |
|----------------------------------------------|-----|
| Minimum distance to an electric cooktop (mm) | 650 |
| Minimum distance to a gas cooktop (mm)       | 650 |
| Recirculation Option                         | √   |
| Charcoal Filter                              | -   |
| Back Draught Shutter                         | No  |
| Inner shield                                 | -   |

**Electric Connection**

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50       |
| Rated power input (W)             | 277      |
| Protection against electric shock | Class II |

**Accessories**

|                                 |          |
|---------------------------------|----------|
| Upper Decorative Duct Extension | 02861301 |
| Back Draught Shutter            | 02832001 |
| Active Charcoal Filter          | 02859398 |