




# SYGMA 6010 BK

Cod. **02060400**

EAN **8422248357289**



## INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248357289 |
| Subfamily | Box           |

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|                                               |      |
|-----------------------------------------------|------|
| AEC (Energy consumption per year) (kWh/año)   | 53,6 |
| EEL class (Energy efficiency class)           | A    |
| FDE (Fluid dynamic efficiency)                | 30,7 |
| FDE class (Fluid dynamic efficiency class)    | A    |
| LE (Light efficiency) (lux/W)                 | 23,1 |
| LE class (Light efficiency class)             | B    |
| GFE (Grease filtering efficiency)             | 91,2 |
| GFE Class (Grease filtering efficiency class) | B    |
| Normal mode airflow MIN (m3/h)                | 340  |
| Normal mode airflow MAX (m3/h)                | 600  |
| Boost mode airflow (m3/h)                     | 802  |
| Normal mode acoustic power MIN (dB)           | 50   |
| Normal mode acoustic power MAX (dB)           | 65   |
| Boost mode acoustic power (dB)                | 67   |
| Po (Off-mode power consumption) (W)           | 0,48 |
| Ps (Stand-by power consumption) (W)           | 0,48 |

### Integration directive EU 66/2014

|                                                               |       |
|---------------------------------------------------------------|-------|
| f (Factor Increase in the time)                               | 0,9   |
| EEL (Energy efficiency Index)                                 | 52,1  |
| QBEP (Maximum airflow point efficiency) (m3/h)                | 443,1 |
| WBEP (Maximum pressure point efficiency) (Pa)                 | 427,1 |
| WBEP (Electrical power consumption at maximum efficiency) (W) | 171   |
| WL (Rated power lighting system) (W)                          | 3     |
| EMIDDLE (Average illuminance on the cooking surface) (lux)    | 69    |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 900      |
| Depth (mm)                | 495      |
| Maximum Total Height (mm) | 990      |
| Minimum Total Height (mm) | 745      |
| Outlet Diameter (mm)      | 150, 125 |

### Characteristics

|                                  |                       |
|----------------------------------|-----------------------|
| Motor Quantity                   | 1                     |
| Motor Model                      | BT3                   |
| Filter Technology                | Aluminium mesh        |
| Control Technology               | Electronic Soft Touch |
| Booster                          | √                     |
| Power levels                     | 4                     |
| Timer                            | √                     |
| Filter Saturation Indicator      | √                     |
| Charcoal Filter Change Indicator | √                     |
| Dimmer Function                  | √                     |
| Connectivity                     | No                    |
| Remote control                   | -                     |
| Display                          | -                     |

### Lighting

|                      |       |
|----------------------|-------|
| Light Model          | SSLED |
| Lightning Technology | LED   |

### Installation

|                                              |     |
|----------------------------------------------|-----|
| Minimum distance to an electric cooktop (mm) | 650 |
| Minimum distance to a gas cooktop (mm)       | 650 |

|                      |    |
|----------------------|----|
| Recirculation Option | √  |
| Charcoal Filter      | -  |
| Back Draught Shutter | No |
| Inner shield         | -  |

---

**Electric Connection**

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50       |
| Rated power input (W)             | 283      |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |

---

**Accessories**

|                         |          |
|-------------------------|----------|
| Back Draught Shutter    | 02832004 |
| Active Charcoal Filter  | 02859398 |
| Noiseless Flexible Duct | 02893002 |

---