



## SK 6000 X

Cod. 02060609

EAN 8422248356978



### INFORMACIÓN GENERAL

EAN/UPC	8422248356978
Subfamily	Box

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (Energy efficiency class)	A
FDE (Fluid dynamic efficiency)	25,6
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	31,6
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	74,6
Normal mode airflow MIN (m3/h)	Installation Drawing
Normal mode airflow MAX (m3/h)	380
Normal mode acustic power MIN (dB)	52
Normal mode acustic power MAX (dB)	1950
Boost mode acustic power (dB)	249

### Integration directive EU 66/2014

<i>f</i> (Factor Increase in the time)	1,1
EEl (Energy efficiency Index)	51,7
QBEP (Maximum airflow point efficiency) (m3/h)	GAOWEI
PBEP (Maximum pressure point efficiency) (Pa)	8414600000
WBEP (Electrical power consumption at maximum efficiency) (W)	56
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

### External Dimensions

Depth (mm)	470
Maximum Total Height (mm)	925
Outlet Diameter (mm)	150

### Characteristics

Motor Quantity	1
Motor Model	K10 390 A
Maximum Pressure (Pa)	293
Filter Technology	Aluminium mesh
Control Tecnology	Mechanical push button
Booster	-
Power levels	3
Timer	170
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	Ise
Connectivity	No
Remote control	-

### Lighting

Light Model	365
Lightning Technology	LED

### Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	-
Charcoal Filter	-
Inner shield	-

### Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50

Rated power input (W)	103
Protection against electric shock	Class II
Power cord length (m)	9,36
Plug type	No plug

---

**Accessories**

Upper Decorative Duct Extension	true302
Back Draught Shutter	'02832004
MAX PRO Metal Filter	'02800917

---