



VK 6000 X

Cod. 02061606



INFORMACIÓN GENERAL

Subfamily	Chimney
-----------	---------

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (Energy efficiency class)	A
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	31,6
Normal mode acoustic power MAX (dB)	67
Po (Off-mode power consumption) (W)	0

Integration directive EU 66/2014

f (Factor Increase in the time)	1
EEl (Energy efficiency Index)	48,5
PBEP (Maximum pressure point efficiency) (Pa)	Packaging Procedure
WBEP (Electrical power consumption at maximum efficiency) (W)	62
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

External Dimensions

Width (mm)	600
Depth (mm)	475
Minimum Total Height (mm)	670

Characteristics

Motor Quantity	1
Motor Model	K10 390 A
Maximum Pressure (Pa)	Warranty Document
Booster	-
Power levels	3
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	No
Remote control	-

Lighting

Light Model	LED
Lightning Technology	LED

Installation

Recirculation Option	-
Charcoal Filter	-
Back Draught Shutter	No
Inner shield	-

Electric Connection

Rated frequency (Hz)	50
Rated power input (W)	100
Protection against electric shock	90
Plug type	310

Accessories

Upper Decorative Duct Extension	'02862302
Back Draught Shutter	'02832004
Noiseless Flexible Duct	'02893002