



## EXTENDER 900

Cod. **02094306**

EAN **8422248110310**



### INFORMACIÓN GENERAL

EAN/UPC	8422248110310
Subfamily	Telescopic

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	44,5
EEL class (Energy efficiency class)	C
FDE (Fluid dynamic efficiency)	11,9
FDE class (Fluid dynamic efficiency class)	E
LE (Light efficiency) (lux/W)	36
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	68
GFE Class (Grease filtering efficiency class)	D
Normal mode airflow MIN (m3/h)	150
Normal mode airflow MAX (m3/h)	390
Normal mode acoustic power MIN (dB)	45
Normal mode acoustic power MAX (dB)	57
Po (Off-mode power consumption) (W)	0
Ps (Stand-by power consumption) (W)	0

### Integration directive EU 66/2014

EEL (Energy efficiency Index)	78,2
QBEP (Maximum airflow point efficiency) (m3/h)	198,2
PBEP (Maximum pressure point efficiency) (Pa)	148
WBEP (Electrical power consumption at maximum efficiency) (W)	68,6
WL (Rated power lighting system) (W)	7

### External Dimensions

Width (mm)	700
Depth (mm)	280
Maximum Total Height (mm)	180
Outlet Diameter (mm)	120

### Characteristics

Motor Quantity	1
Motor Model	570
Maximum Pressure (Pa)	194
Booster	-
Power levels	2
Timer	-
Connectivity	-
Remote control	-
Display	-

### Lighting

Light Model	270D
Lightning Technology	LED

### Installation

Minimum distance to an electric cooktop (mm)	550
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	Packaging Label
Charcoal Filter	FalseLabel
Back Draught Shutter	-
Inner shield	√

### Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	200
Rated power input (W)	107

## Accessories

Upper Decorative Duct Extension	No
White Decorative Duct	No
Black Decorative Duct	No
Island Tube Enhancer	No
Back Draught Shutter	02849003
MAX PRO Metal Filter	No
Active Charcoal Filter	02825263
Noiseless Flexible Duct	No
Recirculating kit	No