




## ISLA FARO BK

Cod. 02119401

EAN 8422248370837



### INFORMACIÓN GENERAL

EAN/UPC	8422248370837
Subfamily	Island

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	613
EEl class (Energy efficiency class)	B
FDE (Fluid dynamic efficiency)	243
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	214
LE class (Light efficiency class)	B
GFE (Grease filtering efficiency)	935
GFE Class (Grease filtering efficiency class)	B
Normal mode airflow MIN (m3/h)	334
Normal mode airflow MAX (m3/h)	5903
Boost mode airflow (m3/h)	7063
Normal mode acoustic power MIN (dB)	54
Normal mode acoustic power MAX (dB)	69
Boost mode acoustic power (dB)	71
Po (Off-mode power consumption) (W)	0,26
Ps (Stand-by power consumption) (W)	0

### Integration directive EU 66/2014

f (Factor Increase in the time)	11
EEl (Energy efficiency Index)	635
QBEP (Maximum airflow point efficiency) (m3/h)	3317
PBEP (Maximum pressure point efficiency) (Pa)	376
WBEP (Electrical power consumption at maximum efficiency) (W)	1425
WL (Rated power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	1283

### External Dimensions

Width (mm)	400
Depth (mm)	400
Maximum Total Height (mm)	1090
Minimum Total Height (mm)	700
Outlet Diameter (mm)	150, 125

### Characteristics

Motor Quantity	1
Motor Model	BT5AC
Maximum Pressure (Pa)	4399
Filter Technology	Malla
Control Technology	Electronic Touch Control
Booster	√
Power levels	4
Timer	√
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	√
Connectivity	No
Remote control	-
Display	-

### Lighting

Light Model	CSLED
Lightning Technology	LED

### Installation

Minimum distance to an electric cooktop (mm)	550
--	-----

Minimum distance to a gas cooktop (mm)	650
Recirculation Option	√
Charcoal Filter	-
Back Draught Shutter	No
Inner shield	√

---

#### Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Rated power input (W)	283
Protection against electric shock	Class II
Power cord length (m)	1100
Plug type	No plug

---

#### Accessories

Back Draught Shutter	02832004
Noiseless Flexible Duct	02893002
Recirculating kit	02800013

---