


PLACAS VITROCERÁMICAS



TN 604

Cod. **08040010**


EAN **8422248058285**











INFORMACIÓN GENERAL

EAN/UPC	8422248058285
Subfamily	Radiant
Product fiche	
Number of cooking zones	4
Zone 1: Technology	Radiant
Zone 1: Zone type	Simple
Zone 1: Position	Front Left
Zone 1: Diameter of the zone (mm)	14
Zone 1: Power (kW)	1,2
Zone 1: Consumption (Wh / kg)	187,7
Zone 1B: Diameter of the zone (mm)	N/A
Zone 1C: Diameter of the zone (mm)	N/A
Zone 1C: Consumption (Wh / kg)	1200
Zone 2: Technology	Radiant
Zone 2: Zone type	Simple
Zone 2: Position	Rear Left
Zone 2: Diameter of the zone (mm)	18
Zone 2: Consumption (Wh / kg)	183,4061841
Zone 2B: Diameter of the zone (mm)	N/A
Zone 2C: Diameter of the zone (mm)	N/A
Zone 3: Technology	FOB Zhongshan (CN)
Zone 3: Zone type	Simple
Zone 3: Position	Rear Right
Zone 3: Diameter of the zone (mm)	14
Zone 3: Power (kW)	1,2
Zone 3C: Diameter of the zone (mm)	N/A
Zone 4: Zone type	236
Zone 4: Position	User Manual
Zone 4: Diameter of the zone (mm)	18
Zone 4: Power (kW)	1,8
Zone 4B: Diameter of the zone (mm)	N/A
Zone 4C: Diameter of the zone (mm)	N/A
Zone 5: Technology	N/A
Zone 5: Zone type	N/A
Zone 5: Diameter of the zone (mm)	150
Zone 5B: Diameter of the zone (mm)	N/A
Zone 5C: Diameter of the zone (mm)	N/A
Zone 6: Technology	N/A
Zone 6: Zone type	Product Identity Declaration
Zone 6: Position	10,9
Zone 6: Diameter of the zone (mm)	N/A
Zone 6B: Diameter of the zone (mm)	N/A
Dimensions	
Width (mm)	590
Depth (mm)	520
Built-in width (mm)	560
Built-in depth (mm)	490
Easy installation System	Quick Fix
Finishing	
Material	Glass
Bevel	No
Control	
Control Position	Front Centre
Independent control by zone	-
Hidden control	180
Power levels	9
Knob type	N/A

Cooking time programming	=
Countdown alarm	-
Power management	-
Available Power Limits (kW)	No
Connectivity	Pro
Auto Ignition	А
Security	
Security lock	Stainless steel
Child lock	Yes (Key)
Residual heat indicator	\checkmark
Automatic detection of cookware	√
Intelligent detection of cookware	-
Automatic safety shutdown	\checkmark
Liquid spill protection	\checkmark
Safety Valve	-
Electrical connection	
Rated frequency (Hz)	50/60
Rated power input (W)	7,2
Multi Phase Connection Option	No
Protection against electric shock	\checkmark
Power cord length (m)	1
Plug type	No plug
Accessories	