




## Q-7760 BK

Cod. 02148402

EAN 8422248084178



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248084178 |
| Subfamily | Chimney       |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |      |
|---|------|
| AEC (Annual energy consumption) (kWh/year)    | 95,7 |
| EEl class (energy efficiency class)           | C    |
| FDE (fluid dynamic efficiency)                | 17,8 |
| FDE class (fluid dynamic efficiency class)    | D    |
| LE (light efficiency) (Lux/W)                 | 36   |
| LE class (light efficiency class)             | A    |
| GFE (grease filtering efficiency)             | 90,3 |
| GFE class (grease filtering efficiency class) | B    |
| Airflow in normal mode MIN (m3/h)             | 385  |
| Airflow in normal mode MAX (m3/h)             | 645  |
| Acoustic power in normal mode MIN (dB)        | 58   |
| Acoustic power in normal mode MAX (dB)        | 72   |
| Po (energy consumption in off mode) (W)       | 0    |
| Ps (energy consumption in standby mode) (W)   | 0    |

### Integration directive EU 66/2014

|  |       |
|--|-------|
| f (time increase factor)                                   | 1,4   |
| EEl (Energy Efficiency Index)                              | 80,1  |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 371,8 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 314   |
| WBEP (power consumption at maximum efficiency) (W)         | 182,5 |
| WL (nominal power lighting system) (W)                     | 7     |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 252   |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 600      |
| Depth (mm)                | 560      |
| Maximum total height (mm) | 1110     |
| Minimum total height (mm) | 655      |
| Diamètre de sortie (mm)   | 150, 125 |

### Characteristics

|                                       |                        |
|---------------------------------------|------------------------|
| Motor quantity                        | 1                      |
| Motor model                           | TA                     |
| Maximum pressure (Pa)                 | 430                    |
| Filter technology                     | Aluminium mesh         |
| Control technology                    | Mechanical push button |
| Booster                               | -                      |
| Power levels                          | 3                      |
| Timer                                 | -                      |
| Filter saturation indicator           | -                      |
| Charcoal filter replacement indicator | -                      |
| Dimmer function                       | -                      |
| Connectivity                          | -                      |
| Remote control                        | -                      |
| Display                               | -                      |

### Lighting

|                |          |
|----------------|----------|
| Light model    | ECOLED 2 |
| Ray technology | LED      |

### Installation

|   |     |
|---|-----|
| Minimum distance to electric plate (mm) | 650 |
| Minimum distance to gas plate (mm)      | 650 |
| Recirculation option                    | √   |
| Charcoal filter                         | -   |

|                      |   |
|----------------------|---|
| Back draught shutter | - |
| Inner shield         | - |

---

### Electric connection

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50       |
| Nominal input power (W)   | 277      |
| Electric shock protection | Class II |
| Plug type                 | Type C   |

---

### Accessories

|                                 |         |
|---------------------------------|---------|
| Upper decorative duct extension | 2883400 |
| White decorative duct           | No      |
| Black decorative duct           | No      |
| Island tube booster             | No      |
| Back draught shutter            | 2832001 |
| MAX PRO Metal filter            | No      |
| Activated charcoal filter       | 2859391 |
| Noiseless flexible duct         | 2893002 |
| Recirculation kit               | No      |

---