



SK 6000 X

Cod. 02060609

EAN 8422248356978



GENERAL INFORMATION

EAN/UPC	8422248356978
Subfamily	Box

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	25,6
FDE class (fluid dynamic efficiency class)	B
LE (light efficiency) (Lux/W)	31,6
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	74,6
Airflow in normal mode MIN (m3/h)	Installation Drawing
Airflow in normal mode MAX (m3/h)	380
Acoustic power in normal mode MIN (dB)	52
Acoustic power in normal mode MAX (dB)	1950
Acoustic power boost mode (dB)	249

Integration directive EU 66/2014

<i>f</i> (time increase factor)	1,1
EEl (Energy Efficiency Index)	51,7
QBEP (maximum efficiency at air flow point) (m3/h)	GAOWEI
PBEP (maximum efficiency at pressure point) (Pa)	8414600000
WBEP (power consumption at maximum efficiency) (W)	56
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

External Dimensions

Depth (mm)	470
Maximum total height (mm)	925
Diamètre de sortie (mm)	150

Characteristics

Motor quantity	1
Motor model	K10 390 A
Maximum pressure (Pa)	293
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	170
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	Ise
Connectivity	No
Remote control	-

Lighting

Light model	365
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	103

Electric shock protection	Class II
Power cord length (m)	9,36
Plug type	No plug

Accessories

Upper decorative duct extension	true302
Back draught shutter	'02832004
MAX PRO Metal filter	'02800917
