



V3-T600 X

Cod. **02061399**

EAN **8422248095273**



GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248095273 |
| Subfamily | Chimney |

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|---|-------|
| AEC (Annual energy consumption) (kWh/year) | 29,8 |
| EEl class (energy efficiency class) | B |
| FDE (fluid dynamic efficiency) | 13,9 |
| FDE class (fluid dynamic efficiency class) | D |
| LE (light efficiency) (lux/W) | 44 |
| LE class (light efficiency class) | A |
| GFE (grease filtering efficiency) | 65,3 |
| GFE class (grease filtering efficiency class) | D |
| Airflow in normal mode MIN (m3/h) | 166,7 |
| Airflow in normal mode MAX (m3/h) | 346,1 |
| Acoustic power in normal mode MIN (dB) | 51 |
| Acoustic power in normal mode MAX (dB) | 66 |
| Po (energy consumption in off mode) (W) | 0 |

Integration directive EU 66/2014

| | |
|--|-------|
| f (time increase factor) | 1,5 |
| EEl (Energy Efficiency Index) | 66,4 |
| QBEP (maximum efficiency at air flow point) (m3/h) | 202,1 |
| PBEP (maximum efficiency at pressure point) (Pa) | 129 |
| WBEP (power consumption at maximum efficiency) (W) | 52,1 |
| WL (nominal power lighting system) (W) | 1,7 |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 74 |

External Dimensions

| | |
|---------------------------|-----|
| Width (mm) | 595 |
| Depth (mm) | 480 |
| Maximum total height (mm) | 923 |
| Minimum total height (mm) | 573 |
| Diamètre de sortie (mm) | 150 |

Characteristics

| | |
|---------------------------------------|------------------------|
| Motor quantity | 1 |
| Motor model | TT300 |
| Maximum pressure (Pa) | 173,3 |
| Filter technology | Aluminium mesh |
| Control technology | Mechanical push button |
| Power levels | 3 |
| Timer | - |
| Filter saturation indicator | - |
| Charcoal filter replacement indicator | - |
| Dimmer function | - |
| Connectivity | No |
| Remote control | - |
| Display | - |

Lighting

| | |
|----------------|-------|
| Light model | CSLED |
| Ray technology | LED |

Installation

| | |
|----------------------|----------|
| Recirculation option | √ |
| Charcoal filter | - |
| Back draught shutter | Included |
| Inner shield | - |

Electric connection

| | |
|---------------------------|---------|
| Nominal voltage (V) | 220-240 |
| Nominal frequency (Hz) | 50 |
| Nominal input power (W) | 65 |
| Electric shock protection | Class I |
| Plug type | No plug |

Accessories

| | |
|---------------------------|----------|
| Activated charcoal filter | 02859495 |
|---------------------------|----------|
