




ISLA MAGRABA

Cod. 02119207

EAN 8422248069342



GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248069342 |
| Subfamily | Island |

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|---|------|
| AEC (Annual energy consumption) (kWh/year) | CATA |
| EEl class (energy efficiency class) | C |
| FDE (fluid dynamic efficiency) | 15,7 |
| FDE class (fluid dynamic efficiency class) | D |
| LE (light efficiency) (Lux/W) | 130 |
| LE class (light efficiency class) | D |
| GFE (grease filtering efficiency) | 91,2 |
| GFE class (grease filtering efficiency class) | B |
| Airflow in normal mode MIN (m3/h) | 300 |
| Acoustic power in normal mode MIN (dB) | 48 |
| Po (energy consumption in off mode) (W) | 0,26 |
| Ps (energy consumption in standby mode) (W) | 0 |

Integration directive EU 66/2014

| | |
|--|------------------|
| <i>f</i> (time increase factor) | 1,4 |
| EEl (Energy Efficiency Index) | 84,1 |
| PBEP (maximum efficiency at pressure point) (Pa) | 253 |
| WL (nominal power lighting system) (W) | EXW Torello (SP) |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 150 |

External Dimensions

| | |
|---------------------------|-----|
| Width (mm) | 650 |
| Depth (mm) | 270 |
| Minimum total height (mm) | 720 |

Characteristics

| | |
|-----------------------------|--------------|
| Motor quantity | 1 |
| Motor model | BT2 |
| Maximum pressure (Pa) | 190 |
| Filter technology | uminium mesh |
| Control technology | 620 |
| Booster | - |
| Power levels | 3 |
| Timer | √ |
| Filter saturation indicator | - |
| Connectivity | - |
| Display | 160 |

Lighting

| | |
|----------------|----------|
| Light model | ECOLED 2 |
| Ray technology | LED |

Installation

| | |
|---|--------|
| Minimum distance to electric plate (mm) | 650 |
| Minimum distance to gas plate (mm) | Active |
| Charcoal filter | 22 |
| Inner shield | - |

Electric connection

| | |
|-------------------------|-----------------|
| Nominal voltage (V) | 220-240 |
| Nominal frequency (Hz) | 50 |
| Nominal input power (W) | Circuit diagram |

Accessories

| | |
|---------------------------------|----|
| Upper decorative duct extension | No |
| White decorative duct | No |

| | |
|---------------------------|----|
| Black decorative duct | No |
| Island tube booster | No |
| Back draught shutter | No |
| MAX PRO Metal filter | No |
| Activated charcoal filter | No |
| Noiseless flexible duct | No |
| Recirculation kit | No |