




# CK 9000 X

Cod. 02008107

EAN 8422248356992



## GENERAL INFORMATION

EAN/UPC	8422248356992
Subfamily	Curved Glass

## Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	24,7
EEl class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	25,6
FDE class (fluid dynamic efficiency class)	B
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	74,6
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	Exportaction
Airflow in normal mode MAX (m3/h)	380
Acoustic power in normal mode MIN (dB)	52
Acoustic power in normal mode MAX (dB)	68
Po (energy consumption in off mode) (W)	0

## Integration directive EU 66/2014

f (time increase factor)	GAOWEI
EEl (Energy Efficiency Index)	51,7
QBEP (maximum efficiency at air flow point) (m3/h)	216,1
PBEP (maximum efficiency at pressure point) (Pa)	238,5
WBEP (power consumption at maximum efficiency) (W)	56
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

## External Dimensions

Width (mm)	900
Height (mm)	50
Depth (mm)	470
Maximum total height (mm)	915
Minimum total height (mm)	670
Diamètre de sortie (mm)	9,36

## Characteristics

Motor quantity	1
Motor model	K10 390 A
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	Ise
Power levels	3
Timer	1116
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-

## Lighting

Light model	CSLED
Ray technology	LED

## Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Back draught shutter	No
Inner shield	-

**Electric connection**

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	103
Electric shock protection	Class II
Plug type	No plug

**Accessories**

Back draught shutter	'02832004
Activated charcoal filter	\$