




ISLA FARO BK

Cod. 02119401

EAN 8422248370837



GENERAL INFORMATION

EAN/UPC	8422248370837
Subfamily	Island

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	613
EI class (energy efficiency class)	B
FDE (fluid dynamic efficiency)	243
FDE class (fluid dynamic efficiency class)	B
LE (light efficiency) (Lux/W)	214
LE class (light efficiency class)	B
GFE (grease filtering efficiency)	935
GFE class (grease filtering efficiency class)	B
Airflow in normal mode MIN (m3/h)	334
Airflow in normal mode MAX (m3/h)	5903
Airflow in boost mode MIN (m3/h)	7063
Acoustic power in normal mode MIN (dB)	54
Acoustic power in normal mode MAX (dB)	69
Acoustic power boost mode (dB)	71
Po (energy consumption in off mode) (W)	0,26
Ps (energy consumption in standby mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	11
EI (Energy Efficiency Index)	635
QBEP (maximum efficiency at air flow point) (m3/h)	3317
PBEP (maximum efficiency at pressure point) (Pa)	376
WBEP (power consumption at maximum efficiency) (W)	1425
WL (nominal power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	1283

External Dimensions

Width (mm)	400
Depth (mm)	400
Maximum total height (mm)	1090
Minimum total height (mm)	700
Diamètre de sortie (mm)	150, 125

Characteristics

Motor quantity	1
Motor model	BT5AC
Maximum pressure (Pa)	4399
Filter technology	Malla
Control technology	Electronic Touch Control
Booster	√
Power levels	4
Timer	√
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	√
Connectivity	No
Remote control	-
Display	-

Lighting

Light model	CSLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	550
Minimum distance to gas plate (mm)	650

Recirculation option	√
Charcoal filter	-
Back draught shutter	No
Inner shield	√

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	283
Electric shock protection	Class II
Power cord length (m)	1100
Plug type	No plug

Accessories

Back draught shutter	02832004
Noiseless flexible duct	02893002
Recirculation kit	02800013
