




CK 9000 X

Cod. 02008107

EAN 8422248356992



GENERAL INFORMATION

EAN/UPC	8422248356992
Subfamily	Curved Glass

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	24,7
EEl class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	25,6
FDE class (fluid dynamic efficiency class)	B
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	74,6
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	Exportaction
Airflow in normal mode MAX (m3/h)	380
Acoustic power in normal mode MIN (dB)	52
Acoustic power in normal mode MAX (dB)	68
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	GAOWEI
EEl (Energy Efficiency Index)	51,7
QBEP (maximum efficiency at air flow point) (m3/h)	216,1
PBEP (maximum efficiency at pressure point) (Pa)	238,5
WBEP (power consumption at maximum efficiency) (W)	56
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

External Dimensions

Width (mm)	900
Height (mm)	50
Depth (mm)	470
Maximum total height (mm)	915
Minimum total height (mm)	670
Diamètre de sortie (mm)	9,36

Characteristics

Motor quantity	1
Motor model	K10 390 A
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	Ise
Power levels	3
Timer	1116
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-

Lighting

Light model	CSLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Back draught shutter	No
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	103
Electric shock protection	Class II
Plug type	No plug

Accessories

Back draught shutter	'02832004
Activated charcoal filter	\$