



DUCT IN-LINE 200/910

Cod. **00706000**

EAN **8422248021289**

GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248021289 |
| Subfamily | In Line |

General features

| | |
|--|--------------|
| Motor type | AC/INDUCTION |
| Motor power (W) | 65;85;55 |
| Lighting technology | N/A |
| Light quantity | N/A |
| Filter type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | 3 |
| Timer | - |
| Hygro timer | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

Installation

| | |
|---------------------------|-------|
| Width (mm) | 353,6 |
| Height (mm) | 278,5 |
| Depth (mm) | 211 |
| Total minimum height (mm) | 2300 |
| Outlet diameter (mm) | 197 |
| Maximum pressure (Pa) | 225 |
| Anti-return flap included | - |
| Easy installation system | No |

Power connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230 |
| Nominal frequency (Hz) | 50 |
| Nominal input power (W) | 85;65;55 |
| Electric shock protection | Class II |
| Plug type | No plug |

Accessories

| | |
|-----------------|---------|
| Switching speed | 1142001 |
|-----------------|---------|

Power and water connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230 |
| Nominal frequency (Hz) | 50 |
| Nominal input power (W) | 85;65;55 |
| Electric shock protection | Class II |
| Plug type | No plug |

