




## LEGEND 700 X

Cod. **02021306**

EAN **8422248068659**



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248068659 |
| Subfamily | Box           |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |      |
|---|------|
| AEC (Annual energy consumption) (kWh/year)    | 42,1 |
| EEl class (energy efficiency class)           | A    |
| FDE (fluid dynamic efficiency)                | 31,7 |
| FDE class (fluid dynamic efficiency class)    | A    |
| LE (light efficiency) (Lux/W)                 | 36   |
| LE class (light efficiency class)             | A    |
| GFE (grease filtering efficiency)             | 78,5 |
| GFE class (grease filtering efficiency class) | C    |
| Airflow in normal mode MIN (m3/h)             | 200  |
| Airflow in normal mode MAX (m3/h)             | 524  |
| Airflow in boost mode MIN (m3/h)              | 648  |
| Acoustic power in normal mode MIN (dB)        | 40   |
| Acoustic power in normal mode MAX (dB)        | 64   |
| Acoustic power boost mode (dB)                | 67   |
| Po (energy consumption in off mode) (W)       | 0,41 |
| Ps (energy consumption in standby mode) (W)   | 0    |

### Integration directive EU 66/2014

|  |       |
|--|-------|
| f (time increase factor)                                   | 0,8   |
| EEl (Energy Efficiency Index)                              | 44,8  |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 390,3 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 329   |
| WBEP (power consumption at maximum efficiency) (W)         | 112,6 |
| WL (nominal power lighting system) (W)                     | 7     |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 252   |

### External Dimensions

|                           |          |
|---------------------------|----------|
| Width (mm)                | 700      |
| Depth (mm)                | 505      |
| Maximum total height (mm) | 1035     |
| Minimum total height (mm) | 635      |
| Diamètre de sortie (mm)   | 150, 125 |

### Characteristics

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| Motor quantity                        | 1                                    |
| Motor model                           | BTDCA                                |
| Maximum pressure (Pa)                 | 455                                  |
| Filter technology                     | Aluminium mesh                       |
| Control technology                    | PANEL ELECTRONICO<br>DISPLAY DIGITAL |
| Booster                               | √                                    |
| Power levels                          | 5                                    |
| Timer                                 | √                                    |
| Filter saturation indicator           | √                                    |
| Charcoal filter replacement indicator | -                                    |
| Dimmer function                       | √                                    |
| Connectivity                          | -                                    |
| Remote control                        | -                                    |
| Display                               | Display_grafico                      |

### Lighting

|                |        |
|----------------|--------|
| Light model    | EcoLed |
| Ray technology | LED    |

### Installation

|   |     |
|---|-----|
| Minimum distance to electric plate (mm) | 650 |
|---|-----|

|                                    |     |
|------------------------------------|-----|
| Minimum distance to gas plate (mm) | 650 |
| Recirculation option               | √   |
| Charcoal filter                    | -   |
| Back draught shutter               | -   |
| Inner shield                       | -   |

---

#### Electric connection

|                           |          |
|---------------------------|----------|
| Nominal voltage (V)       | 220-240  |
| Nominal frequency (Hz)    | 50       |
| Nominal input power (W)   | 137      |
| Electric shock protection | Class II |
| Power cord length (m)     | 1,5      |
| Plug type                 | Type C   |

---

#### Accessories

|                                 |         |
|---------------------------------|---------|
| Upper decorative duct extension | 2861301 |
| White decorative duct           | No      |
| Black decorative duct           | No      |
| Island tube booster             | No      |
| Back draught shutter            | 2832004 |
| MAX PRO Metal filter            | 2800917 |
| Activated charcoal filter       | 2859398 |
| Noiseless flexible duct         | 2893002 |
| Recirculation kit               | 2894001 |

---