



CG5-T600 X

Cod. 02005299

EAN 8422248097413



GENERAL INFORMATION

EAN/UPC	8422248097413
Subfamily	Curved Glass

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	46
EEl class (energy efficiency class)	\$
FDE (fluid dynamic efficiency)	204
FDE class (fluid dynamic efficiency class)	C
LE (light efficiency) (lux/W)	4933
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	7386
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	3045
Airflow in normal mode MAX (m3/h)	499
Acoustic power in normal mode MIN (dB)	435
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

EEl (Energy Efficiency Index)	667
QBEP (maximum efficiency at air flow point) (m3/h)	260
PBEP (maximum efficiency at pressure point) (Pa)	270
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

External Dimensions

Width (mm)	1116
Depth (mm)	470
Maximum total height (mm)	776
Diamètre de sortie (mm)	150

Characteristics

Motor quantity	1
Motor model	TT500
Motor power (W)	ropean
Maximum pressure (Pa)	9,3
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-
Display	25

Lighting

Light model	ECOLED
Ray technology	516

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	√
Charcoal filter	-
Back draught shutter	Included
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	123
Electric shock protection	Class I
Plug type	Type F

Accessories

Activated charcoal filter	02859492
---------------------------	----------
