



## TF-5260 X

Cod. 02034310

EAN 8422248082129



### GENERAL INFORMATION

EAN/UPC	8422248082129
Subfamily	Telescopic

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (energy efficiency class)	D
FDE class (fluid dynamic efficiency class)	No
LE (light efficiency) (lux/W)	-
LE class (light efficiency class)	-
GFE class (grease filtering efficiency class)	Painted
Airflow in normal mode MIN (m3/h)	Class I
Acoustic power in normal mode MIN (dB)	54
Acoustic power in normal mode MAX (dB)	-
Po (energy consumption in off mode) (W)	0
Ps (energy consumption in standby mode) (W)	0

### Integration directive EU 66/2014

EEl (Energy Efficiency Index)	No
QBEP (maximum efficiency at air flow point) (m3/h)	198
PBEP (maximum efficiency at pressure point) (Pa)	Plastic
WBEP (power consumption at maximum efficiency) (W)	Aluminium mesh
WL (nominal power lighting system) (W)	-
EMIDDLE (Average illuminance on the cooking surface) (lux)	102

### External Dimensions

Width (mm)	650
Height (mm)	LED E-14
Depth (mm)	280
Maximum total height (mm)	175
Minimum total height (mm)	175

### Characteristics

Motor quantity	2
Motor model	L1N
Control technology	Mechanical slider
Booster	-
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	L1N
Connectivity	No
Remote control	-
Display	112

### Lighting

Light model	30
Ray technology	50
Light quantity	-

### Installation

Minimum distance to electric plate (mm)	550
Recirculation option	√
Back draught shutter	-
Inner shield	-

### Electric connection

Nominal voltage (V)	220-240
Electric shock protection	9,2
Power cord length (m)	1,5
Plug type	-

### Accessories

Upper decorative duct extension	1
White decorative duct	No
Black decorative duct	No
MAX PRO Metal filter	No
Noiseless flexible duct	No
Recirculation kit	No