



V3-T600 WH

Cod. 02061799

EAN 8422248110198



GENERAL INFORMATION

EAN/UPC	8422248110198
Subfamily	Chimney

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (energy efficiency class)	B
FDE (fluid dynamic efficiency)	13,9
FDE class (fluid dynamic efficiency class)	D
GFE (grease filtering efficiency)	65,3
GFE class (grease filtering efficiency class)	D
Airflow in normal mode MIN (m3/h)	166,7
Acoustic power in normal mode MIN (dB)	51
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	1,5
EEl (Energy Efficiency Index)	66,4
PBEP (maximum efficiency at pressure point) (Pa)	129
WBEP (power consumption at maximum efficiency) (W)	52,1
WL (nominal power lighting system) (W)	27,6
EMIDDLE (Average illuminance on the cooking surface) (lux)	74

External Dimensions

Width (mm)	595
Maximum total height (mm)	923
Diamètre de sortie (mm)	150

Characteristics

Motor quantity	1
Filter technology	Aluminium mesh
Control technology	chanical push button
Timer	-
Charcoal filter replacement indicator	650
Dimmer function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Light model	1ED
Ray technology	LED

Installation

Minimum distance to gas plate (mm)	Strip
Charcoal filter	CSLED

Electric connection

Nominal voltage (V)	220-240
Nominal input power (W)	65
Electric shock protection	387,5
Plug type	No plug

Accessories

White decorative duct	√
DUAL Filter (metal + activated charcoal)	3
Activated charcoal filter	329495
Recirculation kit	Installation Drawing

