



B-12 MATIC

Cod. **00925000**

EAN **8422248110709**

GENERAL INFORMATION

| | |
|-----------|---------------|
| EAN/UPC | 8422248110709 |
| Subfamily | Axial |

General features

| | |
|--|----------------|
| Motor type | AC/SHADED POLE |
| Motor model | SP5820 |
| Motor power (W) | 20 |
| Lighting technology | N/A |
| Light quantity | N/A |
| Filter type | N/A |
| Number of layers | N/A |
| Control description | N/A |
| Power levels | 1 |
| Timer | - |
| Hygro timer | - |
| Electronic filter saturation indicator | - |
| Dimmable lighting | - |

Installation

| | |
|---------------------------|-----|
| Width (mm) | 180 |
| Height (mm) | 180 |
| Depth (mm) | 101 |
| Total minimum height (mm) | 180 |
| Outlet diameter (mm) | 118 |
| Anti-return flap included | √ |

Power connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230 |
| Nominal frequency (Hz) | 50/60 |
| Nominal input power (W) | 20 |
| Electric shock protection | Class II |
| Plug type | No plug |

Accessories

| | |
|------------------|------------------------|
| Backdraught seal | With automatic shutter |
|------------------|------------------------|

Power and water connection

| | |
|---------------------------|----------|
| Nominal voltage (V) | 230 |
| Nominal frequency (Hz) | 50/60 |
| Nominal input power (W) | 20 |
| Electric shock protection | Class II |
| Plug type | No plug |

