



# JUNO+ 6000 GWH 220-240V 50/60Hz

Cod. **02027801**

EAN **8422248355650**



## GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248355650 |
| Subfamily | Angle Glass   |

## Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |      |
|---|------|
| AEC (Annual energy consumption) (kWh/year)    | 23,1 |
| EEl class (energy efficiency class)           | A+   |
| FDE (fluid dynamic efficiency)                | 33,5 |
| FDE class (fluid dynamic efficiency class)    | A    |
| LE (light efficiency) (Lux/W)                 | 22,6 |
| LE class (light efficiency class)             | B    |
| GFE (grease filtering efficiency)             | 60,9 |
| GFE class (grease filtering efficiency class) | C    |
| Airflow in normal mode MIN (m3/h)             | 170  |
| Airflow in normal mode MAX (m3/h)             | 385  |
| Airflow in boost mode MIN (m3/h)              | 562  |
| Acoustic power in normal mode MIN (dB)        | 44   |
| Acoustic power in normal mode MAX (dB)        | 61   |
| Acoustic power boost mode (dB)                | 69   |
| Po (energy consumption in off mode) (W)       | 0,27 |
| Ps (energy consumption in standby mode) (W)   | 0    |

## Integration directive EU 66/2014

|  |      |
|--|------|
| f (time increase factor)                                   | 0,9  |
| EEl (Energy Efficiency Index)                              | 38,8 |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 258  |
| PBEP (maximum efficiency at pressure point) (Pa)           | 284  |
| WBEP (power consumption at maximum efficiency) (W)         | 62,6 |
| WL (nominal power lighting system) (W)                     | 5    |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 22,6 |

## External Dimensions

|                           |      |
|---------------------------|------|
| Width (mm)                | 900  |
| Depth (mm)                | 400  |
| Maximum total height (mm) | 1000 |
| Minimum total height (mm) | 820  |
| Diamètre de sortie (mm)   | 150  |

## Characteristics

|                                       |                          |
|---------------------------------------|--------------------------|
| Motor quantity                        | 1                        |
| Motor model                           | T1DC                     |
| Maximum pressure (Pa)                 | 250                      |
| Filter technology                     | Aluminium mesh           |
| Control technology                    | Electronic Touch Control |
| Booster                               | √                        |
| Power levels                          | 6                        |
| Timer                                 | √                        |
| Filter saturation indicator           | √                        |
| Charcoal filter replacement indicator | √                        |
| Dimmer function                       | √                        |
| Connectivity                          | √                        |
| Remote control                        | -                        |
| Display                               | Display_grafico          |

## Lighting

|                |       |
|----------------|-------|
| Light model    | SSLED |
| Ray technology | LED   |

## Installation

|   |     |
|---|-----|
| Minimum distance to electric plate (mm) | 500 |
| Minimum distance to gas plate (mm)      | 650 |

|                      |    |
|----------------------|----|
| Recirculation option | -  |
| Charcoal filter      | -  |
| Back draught shutter | No |
| Inner shield         | -  |

---

**Electric connection**

|                           |         |
|---------------------------|---------|
| Nominal voltage (V)       | 220-240 |
| Nominal frequency (Hz)    | 50/60   |
| Nominal input power (W)   | 110     |
| Electric shock protection | Class I |
| Power cord length (m)     | 1,3     |
| Plug type                 | No plug |

---

**Accessories**

|                           |           |
|---------------------------|-----------|
| Activated charcoal filter | '02859394 |
| Noiseless flexible duct   | '02859394 |

---