



Width (mm)	590
Height (mm)	275
Depth (mm)	520
Built-in width (mm)	570
Built-in depth (mm)	504
Easy installation system	Quick Fix

### External Dimensions

Width (mm)	590
Depth (mm)	520
Maximum total height (mm)	275
Minimum total height (mm)	570
Diamètre de sortie (mm)	150

### Finishing

Material	Glass
Bevel	Front
Frame	No
Cooking supports	N/A

### Characteristics

Motor quantity	1
Motor model	BT4DC
Filter technology	Aluminium mesh
Control technology	TFT
Booster	√
Power levels	6
Timer	√
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	√
Remote control	-
Display	Display

### Control

Control type	TFT
Control position	Front Centre
Independent zone control	-
Hidden control	-
Power levels	9 + Booster
Knob type	N/A
Cooking time programming	√
Power management	-
Available power limits (kW)	No
Connectivity	Auto
Autoignition	N/A

### Safety

Safety lock	√
Child lock	Yes (Key)
Residual heat indicator	√
Automatic cookware detection	√
Smart cookware detection	-
Automatic safety shutdown	√
Liquid spill detection	√
Safety valve	-

### Installation

Recirculation option	-
Charcoal filter	-
Back draught shutter	No
Inner shield	-

### Electrical connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	7335

---

Electric shock protection	Class I
Plug type	No plug

---

#### **Electric connection**

---

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50/60
Nominal input power (W)	7335
Electric shock protection	Class I
Plug type	No plug

---

#### **Accessories**

---

Recirculation kit	02800992 + 02801000
-------------------	---------------------

---