



## SK 6000 X

Cod. 02060609

EAN 8422248356978



### GENERAL INFORMATION

EAN/UPC	8422248356978
Subfamily	Box

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	25,6
FDE class (fluid dynamic efficiency class)	B
LE (light efficiency) (Lux/W)	31,6
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	74,6
Airflow in normal mode MIN (m3/h)	Installation Drawing
Airflow in normal mode MAX (m3/h)	380
Acoustic power in normal mode MIN (dB)	52
Acoustic power in normal mode MAX (dB)	1950
Acoustic power boost mode (dB)	249

### Integration directive EU 66/2014

<i>f</i> (time increase factor)	1,1
EEl (Energy Efficiency Index)	51,7
QBEP (maximum efficiency at air flow point) (m3/h)	GAOWEI
PBEP (maximum efficiency at pressure point) (Pa)	8414600000
WBEP (power consumption at maximum efficiency) (W)	56
WL (nominal power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

### External Dimensions

Depth (mm)	470
Maximum total height (mm)	925
Diamètre de sortie (mm)	150

### Characteristics

Motor quantity	1
Motor model	K10 390 A
Maximum pressure (Pa)	293
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	170
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	Ise
Connectivity	No
Remote control	-

### Lighting

Light model	365
Ray technology	LED

### Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Inner shield	-

### Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	103

Electric shock protection	Class II
Power cord length (m)	9,36
Plug type	No plug

---

**Accessories**

Upper decorative duct extension	true302
Back draught shutter	'02832004
MAX PRO Metal filter	'02800917

---