




# ST-6000 X

Cod. **02060309**

EAN **8422248108683**



## GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248108683 |
| Subfamily | Box           |

## Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |       |
|---|-------|
| AEC (Annual energy consumption) (kWh/year)    | 36,1  |
| EEl class (energy efficiency class)           | C     |
| FDE (fluid dynamic efficiency)                | 9,84  |
| FDE class (fluid dynamic efficiency class)    | E     |
| LE (light efficiency) (lux/W)                 | 39,6  |
| LE class (light efficiency class)             | A     |
| GFE (grease filtering efficiency)             | 72,14 |
| GFE class (grease filtering efficiency class) | D     |
| Airflow in normal mode MIN (m3/h)             | 166   |
| Airflow in normal mode MAX (m3/h)             | 292   |
| Acoustic power in normal mode MIN (dB)        | 58    |
| Acoustic power in normal mode MAX (dB)        | 62,4  |
| Po (energy consumption in off mode) (W)       | 0     |

## Integration directive EU 66/2014

|  |        |
|--|--------|
| <i>f</i> (time increase factor)                            | 1,7    |
| EEl (Energy Efficiency Index)                              | 75,4   |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 171    |
| PBEP (maximum efficiency at pressure point) (Pa)           | 114,29 |
| WBEP (power consumption at maximum efficiency) (W)         | 57,27  |
| WL (nominal power lighting system) (W)                     | 2      |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 79     |

## External Dimensions

|                           |     |
|---------------------------|-----|
| Width (mm)                | 600 |
| Depth (mm)                | 500 |
| Maximum total height (mm) | 998 |
| Minimum total height (mm) | 548 |
| Diamètre de sortie (mm)   | 150 |

## Characteristics

|                                       |                        |
|---------------------------------------|------------------------|
| Motor quantity                        | 1                      |
| Motor model                           | TT300                  |
| Filter technology                     | Aluminium mesh         |
| Control technology                    | Mechanical push button |
| Booster                               | -                      |
| Power levels                          | 3                      |
| Timer                                 | -                      |
| Filter saturation indicator           | -                      |
| Charcoal filter replacement indicator | -                      |
| Dimmer function                       | -                      |
| Connectivity                          | No                     |
| Remote control                        | -                      |
| Display                               | -                      |

## Lighting

|                |              |
|----------------|--------------|
| Light model    | ECOLED STRIP |
| Ray technology | LED          |

## Installation

|   |          |
|---|----------|
| Minimum distance to electric plate (mm) | 65       |
| Minimum distance to gas plate (mm)      | 65       |
| Recirculation option                    | √        |
| Charcoal filter                         | -        |
| Back draught shutter                    | Included |
| Inner shield                            | -        |

**Electric connection**

|                           |         |
|---------------------------|---------|
| Nominal voltage (V)       | 220-240 |
| Nominal frequency (Hz)    | 50/60   |
| Nominal input power (W)   | 67      |
| Electric shock protection | Class I |
| Plug type                 | Type C  |

**Accessories**

|                                 |           |
|---------------------------------|-----------|
| Upper decorative duct extension | '02863305 |
| Back draught shutter            | Yes       |
| Activated charcoal filter       | 02859495  |
| Noiseless flexible duct         | 02893002  |