



VK 6000 X

Cod. 02061606



GENERAL INFORMATION

| | |
|-----------|---------|
| Subfamily | Chimney |
|-----------|---------|

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|--|------|
| EEl class (energy efficiency class) | A |
| FDE class (fluid dynamic efficiency class) | B |
| LE (light efficiency) (lux/W) | 31,6 |
| Acoustic power in normal mode MAX (dB) | 67 |
| Po (energy consumption in off mode) (W) | 0 |

Integration directive EU 66/2014

| | |
|--|---------------------|
| f (time increase factor) | 1 |
| EEl (Energy Efficiency Index) | 48,5 |
| PBEP (maximum efficiency at pressure point) (Pa) | Packaging procedure |
| WBEP (power consumption at maximum efficiency) (W) | 62 |
| WL (nominal power lighting system) (W) | 3 |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 95 |

External Dimensions

| | |
|---------------------------|-----|
| Width (mm) | 600 |
| Depth (mm) | 475 |
| Minimum total height (mm) | 670 |

Characteristics

| | |
|---------------------------------------|-------------------|
| Motor quantity | 1 |
| Motor model | K10 390 A |
| Maximum pressure (Pa) | Warranty document |
| Booster | - |
| Power levels | 3 |
| Charcoal filter replacement indicator | - |
| Dimmer function | - |
| Connectivity | No |
| Remote control | - |

Lighting

| | |
|----------------|-----|
| Light model | LED |
| Ray technology | LED |

Installation

| | |
|----------------------|----|
| Recirculation option | - |
| Charcoal filter | - |
| Back draught shutter | No |
| Inner shield | - |

Electric connection

| | |
|---------------------------|-----|
| Nominal frequency (Hz) | 50 |
| Nominal input power (W) | 100 |
| Electric shock protection | 90 |
| Plug type | 310 |

Accessories

| | |
|---------------------------------|-----------|
| Upper decorative duct extension | '02862302 |
| Back draught shutter | '02832004 |
| Noiseless flexible duct | '02893002 |