


EXTRACCIÓN DUCT IN-LINE



DUCT IN-LINE 125/320

Cod. **00703000**

EAN **8422248021227**



INFORMACIÓN GENERAL

EAN/UPC	8422248021227	
Subfamily	In Line	
General features		
Motor type	AC/INDUCTION	
Motor power (W)	18;40	
Lightning Technology	N/A	
Light Quantity	N/A	
Filter Type	N/A	
Number of layers	N/A	
Control description	N/A	
Power levels	2	
Timer	-	
Timer Hygro	-	
Electronic filter saturation indicator	-	
Dimmable lighting	-	
Installation		
Width (mm)	279	
Height (mm)	232	
Depth (mm)	168	
Total minimum height (mm)	2300	
Outlet diameter (mm)	122	
Maximum pressure (Pa)	150	
Anti-return flap included	-	
Easy installation system	No	
Power connection		
Rated voltage (V)		
nateu voitage (v)	230	
Rated frequency (Hz)	230 50	
Rated frequency (Hz)	50	
Rated frequency (Hz) Rated power input (W)	50 18;40	
Rated frequency (Hz) Rated power input (W) Protection against electric shock	50 18;40 Class II	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type	50 18;40 Class II	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories	50 18;40 Class II No plug	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid	50 18;40 Class II No plug	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid Overpressure shutter	50 18;40 Class II No plug 1920200 1920300	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid Overpressure shutter Speed Switch Power and water connection	50 18;40 Class II No plug 1920200 1920300	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid Overpressure shutter Speed Switch Power and water connection Rated voltage (V)	50 18;40 Class II No plug 1920200 1920300 1142001	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid Overpressure shutter Speed Switch Power and water connection Rated voltage (V)	50 18;40 Class II No plug 1920200 1920300 1142001	
Rated frequency (Hz) Rated power input (W) Protection against electric shock Plug type Accessories Fixed Grid Overpressure shutter Speed Switch Power and water connection Rated voltage (V) Rated frequency (Hz)	50 18;40 Class II No plug 1920200 1920300 1142001 230 50	