




# X-MART 15 INOX

Cod. 01060000

EAN 8422248003698



## INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248003698 |
| Subfamily | Axial         |

### General features

|  |                |
|--|----------------|
| Motor type                             | AC/SHADED POLE |
| Motor Model                            | SP5825         |
| Motor power (W)                        | 25             |
| Lightning Technology                   | N/A            |
| Light Quantity                         | N/A            |
| Filter Type                            | N/A            |
| Number of layers                       | N/A            |
| Control description                    | N/A            |
| Power levels                           | N/A            |
| Timer                                  | -              |
| Timer Hygro                            | -              |
| Electronic filter saturation indicator | -              |
| Dimmable lighting                      | -              |

### Installation

|                           |           |
|---------------------------|-----------|
| Width (mm)                | 194       |
| Height (mm)               | 194       |
| Depth (mm)                | 123,5     |
| Total minimum height (mm) | 2300      |
| Outlet diameter (mm)      | 148       |
| Maximum pressure (Pa)     | 63        |
| Anti-return flap included | √         |
| Easy installation system  | Quick_Flx |

### Power connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 25       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |

### Accessories

|                     |     |
|---------------------|-----|
| Backdraught Shutter | 230 |
|---------------------|-----|

### Power and water connection

|                                   |          |
|-----------------------------------|----------|
| Rated voltage (V)                 | 220-240  |
| Rated frequency (Hz)              | 50/60    |
| Rated power input (W)             | 25       |
| Protection against electric shock | Class II |
| Plug type                         | No plug  |