




# CK 9000 X

Cod. 02008107

EAN 8422248356992



## INFORMACIÓN GENERAL

EAN/UPC	8422248356992
Subfamily	Curved Glass

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	24,7
EEl class (Energy efficiency class)	A
FDE (Fluid dynamic efficiency)	25,6
FDE class (Fluid dynamic efficiency class)	B
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	74,6
GFE Class (Grease filtering efficiency class)	D
Normal mode airflow MIN (m3/h)	Exportaction
Normal mode airflow MAX (m3/h)	380
Normal mode acustic power MIN (dB)	52
Normal mode acustic power MAX (dB)	68
Po (Off-mode power consumption) (W)	0

### Integration directive EU 66/2014

f (Factor Increase in the time)	GAOWEI
EEl (Energy efficiency Index)	51,7
QBEP (Maximum airflow point efficiency) (m3/h)	216,1
PBEP (Maximum pressure point efficiency) (Pa)	238,5
WBEP (Electrical power consumption at maximum efficiency) (W)	56
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

### External Dimensions

Width (mm)	900
Height (mm)	50
Depth (mm)	470
Maximum Total Height (mm)	915
Minimum Total Height (mm)	670
Outlet Diameter (mm)	9,36

### Characteristics

Motor Quantity	1
Motor Model	K10 390 A
Filter Technology	Aluminium mesh
Control Tecnology	Mechanical push button
Booster	Ise
Power levels	3
Timer	1116
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	No
Remote control	-

### Lighting

Light Model	CSLED
Lightning Technology	LED

### Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	-
Charcoal Filter	-
Back Draught Shutter	No
Inner shield	-

**Electric Connection**

Rated voltage (V)	220-240
Rated frequency (Hz)	50
Rated power input (W)	103
Protection against electric shock	Class II
Plug type	No plug

**Accessories**

Back Draught Shutter	'02832004
Active Charcoal Filter	\$