



# CG5-T900 X

Cod. **02008299**

EAN **8422248108102**



## INFORMACIÓN GENERAL

EAN/UPC	8422248108102
Subfamily	Curved Glass

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	48
EEl class (Energy efficiency class)	B
FDE (Fluid dynamic efficiency)	222
FDE class (Fluid dynamic efficiency class)	C
LE (Light efficiency) (lux/W)	4933
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	8287
GFE Class (Grease filtering efficiency class)	C
Normal mode airflow MIN (m3/h)	296
Normal mode airflow MAX (m3/h)	495
Normal mode acustic power MIN (dB)	455
Normal mode acustic power MAX (dB)	66
Po (Off-mode power consumption) (W)	0

### Integration directive EU 66/2014

f (Factor Increase in the time)	12
EEl (Energy efficiency Index)	644
QBEP (Maximum airflow point efficiency) (m3/h)	2875
PBEP (Maximum pressure point efficiency) (Pa)	288
WBEP (Electrical power consumption at maximum efficiency) (W)	1036
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	148

### External Dimensions

Width (mm)	900
Depth (mm)	470
Maximum Total Height (mm)	776
Minimum Total Height (mm)	426
Outlet Diameter (mm)	150

### Characteristics

Motor Quantity	1
Motor Model	TT500
Maximum Pressure (Pa)	435
Filter Technology	Aluminium mesh
Control Tecnology	Mechanical push button
Booster	310
Power levels	3
Timer	-
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	-
Connectivity	No
Remote control	-
Display	-

### Lighting

Light Model	ECOLED
Lightning Technology	Packaging Procedure

### Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	√
Charcoal Filter	-

Back Draught Shutter	Included
Inner shield	-

---

### Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Rated power input (W)	123
Protection against electric shock	Class I
Plug type	Type F

---

### Accessories

Active Charcoal Filter	02859492
Noiseless Flexible Duct	02893002

---