



## V3-T600 WH

Cod. 02061799

EAN 8422248110198



### INFORMACIÓN GENERAL

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248110198 |
| Subfamily | Chimney       |

### Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |       |
|---|-------|
| AEC (Energy consumption per year) (kWh/año)   | 29,8  |
| EEl class (Energy efficiency class)           | B     |
| FDE (Fluid dynamic efficiency)                | 13,9  |
| FDE class (Fluid dynamic efficiency class)    | D     |
| LE (Light efficiency) (lux/W)                 | 44    |
| LE class (Light efficiency class)             | A     |
| GFE (Grease filtering efficiency)             | 65,3  |
| GFE Class (Grease filtering efficiency class) | D     |
| Normal mode airflow MIN (m3/h)                | 166,7 |
| Normal mode airflow MAX (m3/h)                | 346,1 |
| Normal mode acustic power MIN (dB)            | 51    |
| Normal mode acustic power MAX (dB)            | 66    |
| Po (Off-mode power consumption) (W)           | 0     |

### Integration directive EU 66/2014

|   |       |
|---|-------|
| f (Factor Increase in the time)                               | 1,5   |
| EEl (Energy efficiency Index)                                 | 66,4  |
| QBEP (Maximum airflow point efficiency) (m3/h)                | 202,1 |
| PBEP (Maximum pressure point efficiency) (Pa)                 | 129   |
| WBEP (Electrical power consumption at maximum efficiency) (W) | 52,1  |
| WL (Rated power lighting system) (W)                          | 1,7   |
| EMIDDLE (Average illuminance on the cooking surface) (lux)    | 74    |

### External Dimensions

|                           |     |
|---------------------------|-----|
| Width (mm)                | 595 |
| Depth (mm)                | 480 |
| Maximum Total Height (mm) | 923 |
| Minimum Total Height (mm) | 573 |
| Outlet Diameter (mm)      | 150 |

### Characteristics

|                                  |                        |
|----------------------------------|------------------------|
| Motor Quantity                   | 1                      |
| Motor Model                      | TT300                  |
| Maximum Pressure (Pa)            | 173,3                  |
| Filter Technology                | Aluminium mesh         |
| Control Tecnology                | Mechanical push button |
| Power levels                     | 3                      |
| Timer                            | -                      |
| Filter Saturation Indicator      | -                      |
| Charcoal Filter Change Indicator | -                      |
| Dimmer Function                  | -                      |
| Connectivity                     | No                     |
| Remote control                   | -                      |
| Display                          | -                      |

### Lighting

|                      |       |
|----------------------|-------|
| Light Model          | CSLED |
| Lightning Technology | LED   |

### Installation

|                      |          |
|----------------------|----------|
| Recirculation Option | √        |
| Charcoal Filter      | -        |
| Back Draught Shutter | Included |
| Inner shield         | -        |

### Electric Connection

---

|                                   |         |
|-----------------------------------|---------|
| Rated voltage (V)                 | 220-240 |
| Rated frequency (Hz)              | 50      |
| Rated power input (W)             | 65      |
| Protection against electric shock | Class I |
| Plug type                         | No plug |

---

#### **Accessories**

---

|                        |          |
|------------------------|----------|
| Active Charcoal Filter | 02859495 |
|------------------------|----------|

---