




ISLA FARO BK

Cod. 02119401

EAN 8422248370837



INFORMACIÓN GENERAL

EAN/UPC	8422248370837
Subfamily	Island

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Energy consumption per year) (kWh/año)	613
EEl class (Energy efficiency class)	B
FDE (Fluid dynamic efficiency)	243
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	214
LE class (Light efficiency class)	B
GFE (Grease filtering efficiency)	935
GFE Class (Grease filtering efficiency class)	B
Normal mode airflow MIN (m3/h)	334
Normal mode airflow MAX (m3/h)	5903
Boost mode airflow (m3/h)	7063
Normal mode acoustic power MIN (dB)	54
Normal mode acoustic power MAX (dB)	69
Boost mode acoustic power (dB)	71
Po (Off-mode power consumption) (W)	0,26
Ps (Stand-by power consumption) (W)	0

Integration directive EU 66/2014

f (Factor Increase in the time)	11
EEl (Energy efficiency Index)	635
QBEP (Maximum airflow point efficiency) (m3/h)	3317
PBEP (Maximum pressure point efficiency) (Pa)	376
WBEP (Electrical power consumption at maximum efficiency) (W)	1425
WL (Rated power lighting system) (W)	6
EMIDDLE (Average illuminance on the cooking surface) (lux)	1283

External Dimensions

Width (mm)	400
Depth (mm)	400
Maximum Total Height (mm)	1090
Minimum Total Height (mm)	700
Outlet Diameter (mm)	150, 125

Characteristics

Motor Quantity	1
Motor Model	BT5AC
Maximum Pressure (Pa)	4399
Filter Technology	Malla
Control Technology	Electronic Touch Control
Booster	√
Power levels	4
Timer	√
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	√
Connectivity	No
Remote control	-
Display	-

Lighting

Light Model	CSLED
Lightning Technology	LED

Installation

Minimum distance to an electric cooktop (mm)	550
--	-----

Minimum distance to a gas cooktop (mm)	650
Recirculation Option	√
Charcoal Filter	-
Back Draught Shutter	No
Inner shield	√

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50/60
Rated power input (W)	283
Protection against electric shock	Class II
Power cord length (m)	1100
Plug type	No plug

Accessories

Back Draught Shutter	02832004
Noiseless Flexible Duct	02893002
Recirculating kit	02800013
