




OMEGA 900 BK

Cod. **02004410**

EAN **8422248190633**



INFORMACIÓN GENERAL

| | |
|-----------|---------------|
| EAN/UPC | 8422248190633 |
| Subfamily | Chimney |

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

| | |
|---|-------|
| AEC (Energy consumption per year) (kWh/año) | 105,4 |
| EEl class (Energy efficiency class) | C |
| FDE (Fluid dynamic efficiency) | 20 |
| FDE class (Fluid dynamic efficiency class) | C |
| LE class (Light efficiency class) | B |
| GFE (Grease filtering efficiency) | 90,3 |
| GFE Class (Grease filtering efficiency class) | B |
| Normal mode airflow MIN (m3/h) | 385 |
| Normal mode airflow MAX (m3/h) | 645 |
| Normal mode acustic power MIN (dB) | 57,8 |
| Normal mode acustic power MAX (dB) | 71,8 |
| Po (Off-mode power consumption) (W) | 0 |
| Ps (Stand-by power consumption) (W) | 0 |

Integration directive EU 66/2014

| | |
|--|---------------|
| f (Factor Increase in the time) | 8422248087278 |
| EEl (Energy efficiency Index) | 77,6 |
| QBEP (Maximum airflow point efficiency) (m3/h) | 458,1 |
| PBEP (Maximum pressure point efficiency) (Pa) | 333,8 |
| WL (Rated power lighting system) (W) | 6 |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 126 |

External Dimensions

| | |
|---------------------------|---------|
| Width (mm) | 900 |
| Depth (mm) | 500 |
| Maximum Total Height (mm) | 1020 |
| Minimum Total Height (mm) | 720 |
| Outlet Diameter (mm) | Chimney |

Characteristics

| | |
|----------------------------------|------------------------|
| Motor Quantity | 1 |
| Motor Model | TA |
| Filter Technology | Aluminium mesh |
| Control Tecnology | Mechanical push button |
| Booster | - |
| Power levels | 3 |
| Timer | 1000 |
| Filter Saturation Indicator | - |
| Charcoal Filter Change Indicator | - |
| Dimmer Function | - |
| Connectivity | - |
| Remote control | - |
| Display | - |

Lighting

| | |
|----------------------|-------|
| Light Model | CSLED |
| Lightning Technology | LED |

Installation

| | |
|--|-----|
| Minimum distance to an electric cooktop (mm) | 650 |
| Minimum distance to a gas cooktop (mm) | 650 |
| Recirculation Option | √ |
| Charcoal Filter | - |
| Back Draught Shutter | - |
| Inner shield | - |

Electric Connection

| | |
|-----------------------------------|----------|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50 |
| Rated power input (W) | 276 |
| Protection against electric shock | Class II |
| Power cord length (m) | 0,7 |
| Plug type | No plug |

Accessories

| | |
|---------------------------------|----------|
| Upper Decorative Duct Extension | 02862001 |
| White Decorative Duct | No |
| Black Decorative Duct | No |
| Island Tube Enhancer | No |
| Back Draught Shutter | 02832001 |
| MAX PRO Metal Filter | 02800917 |
| Active Charcoal Filter | 02859391 |
| Noiseless Flexible Duct | 02893002 |