



SK 6000 X

Cod. 02060609

EAN 8422248356978



INFORMACIÓN GENERAL

EAN/UPC	8422248356978
Subfamily	Box

Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

EEl class (Energy efficiency class)	A
FDE (Fluid dynamic efficiency)	25,6
FDE class (Fluid dynamic efficiency class)	B
LE (Light efficiency) (lux/W)	31,6
LE class (Light efficiency class)	A
GFE (Grease filtering efficiency)	74,6
Normal mode airflow MIN (m3/h)	Installation Drawing
Normal mode airflow MAX (m3/h)	380
Normal mode acustic power MIN (dB)	52
Normal mode acustic power MAX (dB)	1950
Boost mode acustic power (dB)	249

Integration directive EU 66/2014

<i>f</i> (Factor Increase in the time)	1,1
EEl (Energy efficiency Index)	51,7
QBEP (Maximum airflow point efficiency) (m3/h)	GAOWEI
PBEP (Maximum pressure point efficiency) (Pa)	8414600000
WBEP (Electrical power consumption at maximum efficiency) (W)	56
WL (Rated power lighting system) (W)	3
EMIDDLE (Average illuminance on the cooking surface) (lux)	95

External Dimensions

Depth (mm)	470
Maximum Total Height (mm)	925
Outlet Diameter (mm)	150

Characteristics

Motor Quantity	1
Motor Model	K10 390 A
Maximum Pressure (Pa)	293
Filter Technology	Aluminium mesh
Control Tecnology	Mechanical push button
Booster	-
Power levels	3
Timer	170
Filter Saturation Indicator	-
Charcoal Filter Change Indicator	-
Dimmer Function	Ise
Connectivity	No
Remote control	-

Lighting

Light Model	365
Lightning Technology	LED

Installation

Minimum distance to an electric cooktop (mm)	650
Minimum distance to a gas cooktop (mm)	650
Recirculation Option	-
Charcoal Filter	-
Inner shield	-

Electric Connection

Rated voltage (V)	220-240
Rated frequency (Hz)	50

Rated power input (W)	103
Protection against electric shock	Class II
Power cord length (m)	9,36
Plug type	No plug

Accessories

Upper Decorative Duct Extension	true302
Back Draught Shutter	'02832004
MAX PRO Metal Filter	'02800917
