



TDM 6003 220-240V 50-60Hz

Cod. **08063413**

EAN **8422248357357**



INFORMACIÓN GENERAL

| | |
|-----------|---------------|
| EAN/UPC | 8422248357357 |
| Subfamily | Radiant |

Product fiche

| | |
|------------------------------------|-------------|
| Number of cooking zones | 3 |
| Zone 1: Technology | Radiant |
| Zone 1: Zone type | Simple |
| Zone 1: Position | Front Right |
| Zone 1: Diameter of the zone (mm) | 18 |
| Zone 1: Power (kW) | 1,8 |
| Zone 1: Consumption (Wh / kg) | 1961 |
| Zone 2: Technology | Radiant |
| Zone 2: Zone type | Simple |
| Zone 2: Position | Rear Right |
| Zone 2: Diameter of the zone (mm) | 14 |
| Zone 2: Power (kW) | 1,2 |
| Zone 2: Consumption (Wh / kg) | 1969 |
| Zone 3: Technology | Radiant |
| Zone 3: Zone type | Double |
| Zone 3: Position | Left |
| Zone 3: Diameter of the zone (mm) | 28 |
| Zone 3: Power (kW) | 2,4 |
| Zone 3: Consumption (Wh / kg) | 1847 |
| Zone 3B: Diameter of the zone (mm) | 22 |
| Zone 3B: Power (kW) | 1,5 |

Dimensions

| | |
|--------------------------|-----------|
| Width (mm) | 590 |
| Height (mm) | 52 |
| Depth (mm) | 520 |
| Built-in width (mm) | 560 |
| Built-in height (mm) | 110 |
| Built-in depth (mm) | 490 |
| Easy installation System | Quick Fix |

Finishing

| | |
|------------------|-------|
| Material | Glass |
| Bevel | No |
| Frame | No |
| Cooking supports | N/A |

Control

| | |
|-----------------------------|----------------------|
| Control type | Slider Touch Control |
| Control Position | Front Centre |
| Independent control by zone | √ |
| Hidden control | - |
| Power levels | 9 |
| Knob type | N/A |
| Cooking time programming | √ |
| Countdown alarm | √ |
| Power management | - |
| Connectivity | No |
| Auto Ignition | N/A |

Security

| | |
|-----------------------------------|----|
| Security lock | √ |
| Child lock | No |
| Residual heat indicator | √ |
| Automatic detection of cookware | - |
| Intelligent detection of cookware | √ |
| Automatic safety shutdown | √ |

| | |
|-------------------------|---|
| Liquid spill protection | √ |
| Safety Valve | - |

Electrical connection

| | |
|-----------------------------------|----------|
| Rated voltage (V) | 220-240 |
| Rated frequency (Hz) | 50/60 |
| Rated power input (W) | 3200 |
| Multi Phase Connection Option | 2 phases |
| Protection against electric shock | Class I |
| Power cord length (m) | 1 |
| Plug type | No plug |
